(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization International Bureau



(43) International Publication Date 31 March 2005 (31.03.2005)

PCT

(10) International Publication Number WO 2005/028758 A1

(51) International Patent Classification7: E02D 7/06, 7/08

(21) International Application Number:

PCT/NZ2004/000223

(22) International Filing Date:

17 September 2004 (17.09.2004)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:


528332 528332 22 September 2003 (22.09.2003) NZ 20 August 2004 (20.08.2004) NZ

(71) Applicant (for all designated States except US): RAMET LIMITED [NZ/NZ]; Level 11, Tower One, Shortland Street Centre, 51-53 Shortland Street, Auckland (NZ).

- (72) Inventor; and
- (75) Inventor/Applicant (for US only): KENNETT, David [NZ/NZ]; P O Box 24-422, Royal Oak, Auckland (NZ).
- (74) Agents: ADAMS, Matthew, D et al.; A J Park, 6th Floor Huddart Parker Building, PO Box 949, Wellington, 6015 (NZ).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH,

[Continued on next page]

(54) Title: ELECTRIC POST DRIVER



(57) Abstract: An impact driver (102) for driving elongate objects (51) into a body, the impact driver comprising of a chassis (3), a ram (18) supported by the chassis in a manner allowing rectilinear movement of the ram relative to the chassis between two limits, a linear induction (16) motor having a stator mounted to the chassis and positioned to operatively interact with a linear induction motor reaction means (15) being of a conductive metal material, the reaction means carried by the ram in a manner to allow the ram to oscillate between the two limits by the stator of the linear induction motor, a first limit being a retracted position and a second limit being an impact position to which the ram is accelerated from the retracted condition by the stator and at which the ram imparts an impact force on the elongate object in the elongate direction thereof.



WO 2005/028758 A1



GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.